

USA-010

- 2 -

AI offers can result from the desire to vend larger portions of products such as the twenty-ounce soda bottle verse the twelve-ounce soda can. In other cases the higher priced items can be items that until recently may not have been considered for sale through vending equipment such as phone cards, disposable cameras, and frozen food entrees to name a few.

Item #2

Replace the paragraph on page 2 lines 11-20 with the following paragraph:

AD The vending industry's desire to vend higher priced items has given rise to issues related to currency and inventory. For example, with the shift to vending twenty-ounce bottles many of the vending sales now involve more that one currency note, as an example two one-dollar bills to make a purchase. As a result the bill validator can fill to capacity with currency notes before all the items in the vending equipment have been sold. With a bill acceptor filled to capacity the vending equipment may not be able to transact another vending sale and place itself out-of-service. As a result vending operators can typically find themselves restocking vending equipment that still has product available for sale but because of the inability to take additional currency notes the vending equipment could not sell the inventory.

Item #3

Replace the paragraph on page 3 lines 6-14 with the following paragraph:

AB In addition to the new burden on bill acceptors and coin mechanism resultant from the sale of higher priced items other issues related to the vending of higher priced items can arise. One such issue can be that a customer may not have enough money on-hand to effectuate the vending purchase. In the case of phone cards, cameras, and frozen food vend prices may range from several dollars to forty dollars, fifty dollars, or more. In

USA-010

- 3 -

many cases the customer may have the desire to purchase the high priced item but simply lacks the amount of currency required to effectuate the purchase. In other cases the customer may be reluctant to trust the vend worthiness of the vending equipment with what the customer considers to be a significant amount of money.

Item #4

Replace the paragraph on page 6 lines 8-15 with the following paragraph:

The present invention also relates to a system having a plurality of configurable communication options for data communicating to a plurality of remote locations. Such communication options include local area network connection, telephone line, wireless point-to-point where the system data communicates wirelessly to a local transceiver base unit which has access to a telephone line thereby giving the system wireless access to a telephone line, and wireless network data communication access, wherein a data modem connects the system to a WAN for data communication access to a plurality of remote locations.

Item #5

Replace the paragraph on page 7 lines 7-8 with the following paragraph:

The present invention also relates to the system 500 being packaged in a semiconductor creating a single chip system 500 solution.

Item #6

Replace the paragraph on page 9 lines 1-3 with the following paragraph:

USA-010

- 4 -

Q16 Figure 9B there is shown an audit-credit-interactive system 500 interfacing to a vending machine MDB bus and interfacing to a plurality of peripheral devices by way of a system 500 mimic MDB bus;

[Item #7

Replace the paragraph on page 9 lines 5-8 with the following paragraph:

Q17 Figure 9C there is shown an audit-credit-interactive system 500 with card reader and audit functionality embodiment interfacing to a vending machine MDB bus and interfacing to a plurality of peripheral devices by way of a system 500 mimic MDB bus;

[Item #8

Replace the paragraph starting on page 10 line 22 through page 11 line 5 with the following paragraph:

Q18 Vending machine types suitable for interconnection to and operation with the VIU 100 include vending beverage and snack machines, value adding equipment, and dispensing equipment that operate in connection with or make available an MDB bus interface, or DEX interface, or a bill acceptor interface, or a coin mechanism interface. Such vending machines include for example and not limitation those manufactured by or for COKE-A-COLA, PEPSI, MARS, VENDO, ROYAL, DLXIE NARCO, GPL, CRANE NATIONAL, AUTOMATED PRODUCTS, CAVALIER, MARCONI or other similar vending machines. Such value adding equipment and dispensing equipment can include for example and not limitation those manufactured by or for ACT, XCP, SCHLUMBERGH, DAYNL, GILBARCO, MARCONI, COPICO, PRE-PAID EXPRESS, or other similar value adding equipment and dispensing equipment.

USA-010

- 5 -

Item #9

Replace the paragraph on page 11 lines 11-13 with the following paragraph:

ag
Audit-credit-interactive system 500 electronics are included within the VIU 100. Many of the electrical interfaces, ports, and connectors shown in Figure 1 are actually electrical connection to the audit-credit-interactive system 500.

Item #10

Replace the paragraph on page 12 lines 1-13 with the following paragraph:

alio
VIU 100 also includes auxiliary interface port 104 and 106. Though general purpose in nature in an exemplary embodiment ports 104, and 106 provide electrical connections to printer interface 532, and external modem interface 528 respectively. The ports 104, and 106 can be RS232, RS484, or other desirable type of communication interface port. Furthermore ports 104, and 106 can be configured for use as required by the desired application. In an exemplary embodiment auxiliary interface port 104 can be used for interfacing to a serial style printer and port 106 can be used to interface to external communication equipment such as data modem, CDMA modems, CDPD modem, wireless transceivers, wireless systems, or other types of communication devices. In an exemplary embodiment an AES wireless transceiver can be used to provide data communication to and from the VIU 100 as well as serve as repeater to receive and re-transmit data communication to and from other VIU 100 types of devices in the geographical area.

Item #11

Replace the paragraph on page 13 lines 16-25 with the following paragraph:

USA-010

- 6 -

Q11
VIU 100 also includes a general-purpose input-output interface 118. The general-purpose input-output interface provides electrical connections to the bill and coin interface 506. In an exemplary embodiment the VIU 100 can be interconnected with vending, valuing, and dispensing equipment by way of the host equipment's bill acceptor or coin interface port. This allows the VIU 100 by way of the bill and coin interface 506 and interface 118 to be original equipment manufactured (OEM) into or retrofitted to vending, valuing, and dispensing equipment that utilize a serial or pulse style bill acceptor, or a coin mechanism interface. Serial and pulse style bill acceptors include for example and not limitation those manufactured for or by MARS, COINCO, CONLUX, ARDAK, or other similar bill acceptor and manufacturers of bill acceptors.

[Item #12

Replace the paragraph on page 14 lines 1-4 with the following paragraph:

Q12
The VIU 100 includes a service button 120 and a ground terminal 122. The service button provides one of a plurality of electrical connections to the keypad and button inputs 510. The ground terminal 122 provides, as may be required, electrical connection to the VIU 100 enclosure.

[Item #13

Replace the paragraph on page 14 lines 11-19 with the following paragraph:

Q13
Referring to Figure 2 there is shown a transceiver and modem base unit 200. Transceiver and modem base unit 200 includes transceiver unit 700 built in. The transceiver unit 200 with transceiver unit 700 data communicates wirelessly with the VIU 100 and by way of a modem data communicates with a remote location. In an exemplary embodiment the VIU 100 with system 500 and transceiver unit 200 with transceiver unit 700 form a wireless data link, which has access to a modem for data communicating with

Q

USA-010

- 7 -

Q13
a remote location. In this regard, the reliance on having a telecommunication line in proximity to the VIU 100 or more generally in proximity to the vending equipment the VIU 100 is installed in is greatly reduced.

Item #14

Replace the paragraph starting on page 17 line 25 through page 18 line 5 with the following paragraph:

Q14
In an exemplary embodiment a VIU 100 can be located inside the vending equipment, such as vending equipment 402. In addition, the card reader assembly with optional printer assembly can be mounted inside the vending equipment in such a way that a user has access to the card reader assembly. During operation a communication line can be interconnected directly with the VIU 100. Alternatively the VIU can wireless data communicate with a transceiver base unit 200. There is shown in Figure 4 a transceiver unit 200 plugged into an electrical outlet on wall 202. Also shown is a telecommunication line 408 interconnect with transceiver unit 200.

Item #15

Replace the paragraph on page 18 lines 13-18 with the following paragraph:

Q15
The audit-credit-interactive system 500 provides three major components of functionality. As an audit device the audit-credit-interactive system 500 can audit inventory, sales, operational and other vending machine performance by way of the MDB and DEX interfaces. This gathering and forwarding to a plurality of remote locations of the DEX and or MDB data can be referred to as vending equipment telemetry, or as telemetry data.

USA-010

- 8 -

Item #16

Replace the paragraph on page 19 lines 4-17 with the following paragraph:

9/16

The audit-credit-interactive system 500 includes numerous mutually exclusive interfaces and control means. In a plurality of customer specifications and where customer cost considerations demand, there may arise a situation where an audit-credit-interactive system 500 may be manufactured in such a way as to not contain or require the use of certain features, functions, interfaces, and or control means. Accordingly, an audit-credit-interactive system 500 can easily be manufactured to include or exclude a specific combination of features, functions, interfaces, and or control means to produce the desired system performance at a desirable cost to a customer. For example and not limitation, a customer may desire to operate an audit-credit-interactive system 500 without an RFID interface 504. In such a case, an audit-credit-interactive system 500 could be manufactured with the omission of the RFID interface 504. In any combination, the same inclusion or exclusion of features, functions, interfaces and or control means can be applied to other audit-credit-interactive system 500 features, functions, interfaces, and or control means.

Item #17

Replace the paragraph on page 19 lines 19-26 with the following paragraph:

9/17

Interconnected with microcontroller 502 can be an RFID interface 504. The RFID interface 502 can data communicate with wired or wireless devices that are proximate to the RFID interface 504. In an exemplary embodiment these wired and wireless devices include, for example and not limitation, touch devices from DALLAS SEMICONDUCTOR, and wireless devices such as the MOBIL SPEED PASS, or other similar or suitable wired or wireless RFID devices. Microcontroller 502 can be any

USA-010

- 9 -

am
suitable microcontroller, or microprocessor. In an exemplary embodiment a microcontroller 502 can be a ZILOG Z8038220FSC.

Item #18

Replace the paragraph on page 20 lines 1-12 with the following paragraph:

ai8
Interconnected with microcontroller 502 can be bill acceptor and coin mechanism interface 506. The bill acceptor and coin mechanism interface 506 emulate industry standard bill acceptor and coin mechanism interfaces. In this regard, the audit-credit-interactive system 500 can be interconnected to vending equipment by way of the interface 506. The audit-credit-interactive system 500 mimicking industry standard bill acceptor and coin mechanism electrical control system and signal timing can then operate the vending equipment. Industry standard bill acceptors include serial and pulse style. Serial style bill acceptors utilize INTERRUPT, SEND, ACCEPT ENABLE, and DATA control signal lines. Pulse style bill acceptor and coin mechanism send electrical pulses to an attached control system to indicated the receipt of coin and currency. Serial and pulse style bill acceptors and coin mechanisms can include for example and not limitation MARS, COINCO, CONLUX, or other similar bill acceptors and or coin mechanisms.

Item #19

Replace the paragraph on page 20 lines 14-19 with the following paragraph:

ai9
Interconnected with microcontroller 502 can be a display interface 508. A display interface 508 can be a liquid crystal display (LCD), an RS232 connection, and or an electrical interface for driving a display. In an exemplary embodiment display interface 508 can be, for example and not limitation, an RS232 serial connection. Such a serial connection can be utilized to data communicate display data as well as other types of data to a card reader interface board 312.

a

USA-010

- 10 -

Item #20

Replace the paragraph on page 21 lines 23-27 with the following paragraph:

Interconnected with microcontroller 502 can be an external peripheral interface 536. The external peripheral interface 536 includes a plurality of configurable input and output lines for interfacing to external peripheral devices. External peripheral interface 536 can support serial peripheral interfaces (SPI), serial interfaces such as RS232, RS485, I²C, and other types of peripheral interfaces and communication protocols and standards.

Item #21

Replace the paragraph on page 22 lines 16-22 with the following paragraph:

In accordance with NAMA and other derivative MDB specifications the MDB interface 518 operates in the slave mode being responsive to the vending machine controller (VMC). The VMC typically resides in the vending equipment and operates as the vending equipment's control system. Interconnection with the MDB bus in combination with NAMA and other derivative MDB standard data communications allows the audit-credit-interactive system 500 to reside as a peripheral device to the vending equipment's control system in an auditing and payment device mode of operation.

Item #22

Replace the paragraph on page 25 lines 12-15 with the following paragraph:

In addition to accepting magnet cards card reader interface 526 can implement a smart card reader interface. In this regard, system 500 by way of card reader interface

USA-010

- 11 -

022

526 can read, write, and execute embedded applications on a plurality of types and brands of smart cards.

Item #23

Replace the paragraph starting on page 27 line 26 through page 28 line 4 with the following paragraph:

023

In a second mode of operation the G4 can be configured and serve as an MDB controller (system 500) only. In this mode both the MDB-CONTROL and NON-MDB-CONTROL commands can be executed. While in this mode of operation the computing platform operates as a master device controlling the operation and process flow of the system. While in this mode the G4 serves as a slave device interfacing to the vending machine and managing the control of the MDB interface.

Item #24

Replace the paragraph on page 28 lines 16-18 with the following paragraph:

024

Serial communications between the computing platform and the MDB controller/G4 are set at 9600 baud, 8 data bits, no parity, and 2 stop bits. Required serial port communications lines include transmit (Txd), Receive (Rxd) and Ground (Gnd).

Item #25

Replace the paragraph starting on page 37 lines 12-19 with the following paragraph:

- 025
2. When the MDB capture mode is switched to 'ON' the G4 will stay in this state until either 1) the buffer area for MDB codes is filled (about 15 seconds) or 2) the MDB capture mode is switched to 'OFF'. Even if the G4 is powered 'OFF' or the @<esc> K HARDWARE RESET command is issued the MDB capture mode
- a

USA-010

- 12 -

Q25

state will not change. The reason for this is to allow the MDB capture mode to be turned 'ON' and remain 'ON' capturing MDB transaction codes between the vending machine and the G4 while the vending machine and or G4 go through a power up or reset procedure.

Item #26

Replace the paragraph starting on page 42 line 26 through page 43 line 4 with the following paragraph:

Q26

@<esc>W – SEND ALL TRANSACTION RECORDS. The MDB controller/G4

will return all the transaction records beginning with 0000. The G4 will return the message 'DONE' when complete. The transaction records are a fixed length records and follow the format shown above in the @<esc>Q command. The result sting will return:

Item #27

Replace the paragraph on page 43 lines 19-22 with the following paragraph:

Q27

If the G4 is in a vending transaction a SEND ALL TRANSACTION RECORDS transaction cannot be executed. If a SEND ALL TRANSACTION RECORDS transaction cannot be executed the result string will return:

Item #28

Replace the paragraph on page 49 lines 20-25 with the following paragraph:

Q28

1. The NOVRAM memory dedicated to the storage of DEX data is cleared.

USA-010

- 13 -

- Q29
2. The G4 will begin recording both the received DEX codes from the vending machine controller (VMC) and the sent DEX codes from the G4. There is RAM room for approximately 6K bytes of recorded DEX data.

Item #29

Replace the paragraph on page 51 lines 1-6 with the following paragraph:

- Q29
1. The NOVRAM memory dedicated to the storage of DEX data is cleared.
 2. The G4 will begin recording both the received DEX codes from the vending machine controller (VMC) and the sent DEX codes from the G4. There is RAM room for approximately 6K bytes of recorded DEX data.

Item #30

Replace the paragraph on page 54 lines 3-9 with the following paragraph:

Q30

The communication pins Rxd, Txd, CTS, and RTS conform to RS232 standards. A minimum of Rxd, Txd, and GND are required to implement serial communication between the G4 and a computing platform. The RTS and CTS lines only come into play from a flow control perspective when receipt data is being sent from the G4. CTS and RTS are implemented in such a way as to allow a receipt printer that has little to no printer buffer to control the flow of data. CTS and RTS have no other purpose in non-print data communications and can be ignored or left unimplemented.

Item #31

Replace the paragraph starting on page 61 line 20 through page 62 line 2 with the following paragraph:

USA-010

- 14 -

031

For example and not limitation print data can be packaged with the format and control codes outlined in the interactive interface protocol and specification shown in the table above. Upon the data arriving at microcontroller 602, microcontroller 602 can decode that the data is print data, remove any protocol formatting characters to obtain pure print data, and then pass or forward the data to the printer interface 608. Similar processes can occur for the other peripheral devices including I/O interface 604, display 606, and card reader interface 610, and keypad and button inputs 612. Data can also [n]be obtained from each of the peripheral devices and combined into a single data string. The data string can be sent to the system 500 where processing can occur based in part of the data string received.

032

Item #32

Replace the paragraph on page 62 lines 15-22 with the following paragraph:

032

In an exemplary embodiment the transceiver unit 700 forms a wireless data link with a VIU 100 having a system 500 incorporated within. In this regard, the requirement of physically connecting the VIU 100 to a communication line can be eliminated. To create a wireless data line the VIU 100 equipped with an audit-credit-interactive system 500 utilizes transceiver 524 to data communicate with transceiver unit 700's transceiver 708. Transceiver 708 is interconnected with microcontroller 702. An antenna 716 is interconnected with transceiver 708. Antenna 716 can be of similar form and function to antenna 538.

033

Item #33

Replace the paragraph on page 63 lines 1-6 with the following paragraph:

033

A plurality of remote locations can include credit bureaus such as processing bureau 804, host network centers such a host network center 808, and other remote

USA-010

- 15 -

Q33
locations such as remote location 806. Processing bureau 804, host network center 808, and remote location 806 can be referred to as a plurality of remote locations or remote locations. Processing bureau 804 can be a credit card processing bureau.

Item #34

Replace the paragraph on page 63 lines 13-20 with the following paragraph:

Q34
Referring to Figure 8 there is shown an audit-credit-interactive system 500 interfaced to a computing platform. Figure 8 illustrates how a audit-credit-interactive system 500 can be connected to a computing platform 802 by way of system 500's interactive interface 532 and computing platform 802 interactive interface. In similar form and function as the interactive interface solution between system 500 and system 600 described above, system 500 and computing platform 802 can interconnect and data communicate as described with the communication specification and protocol shown in the table above.

Item #35

Replace the paragraph on page 65 lines 19-26 with the following paragraph:

Q35
Figure 9B illustrates how an audit-credit-interactive system 500 can be configured in series with the vending machine MDB interface 902. In this regard the peripheral devices can be supported by the system 500's mimic MDB interface 516. The advantage off this network configuration is that the system 500 can support multiple versions and derivative versions of the NAMA MDB protocol specification. Furthermore, the system 500 can provide peripheral message emulation and message passing to effectuate the VMC's ability to data communicate to each peripheral by way of the system 500's MDB interface 518 and mimic MDB interface 516.

USA-010

- 16 -

Item #36

Replace the paragraph starting on page 67 line 23 through page 68 line 2 with the following paragraph:

Q36 Referring to Figure 10A there is shown an audit-credit-interactive system 500 embodied in a semiconductor package 1002. In an exemplary embodiment a complete system 500 can be manufactured into a single semiconductor. This type of manufacture can have the advantage of small size and low cost. In addition, such a semiconductor version of an audit-credit-interactive system 500 can be advantageous when integration of system 500's functionality into other electronic devices is desirable.

Item #37

Replace the paragraph starting on page 72 line 17 through page 73 line 2 with the following paragraph:

Q37 The MDB protocol involves a master-slave relationship between the master vending equipment's VMC and the slave peripheral devices. In implementing the MDB protocol the master VMC initiates an MDB message command to a slave peripheral device. The slave peripheral device then has a finite amount of time to respond to the VMC command message with a message response. As such the amount of time allotted for the peripheral device to respond with a MDB message response can vary from VMC to VMC. If for example and not limitation the peripheral device responds too quickly with a message response the VMC's microprocessor may not be ready and miss the return message. As a result the system 500 could fail to initialize and operate correctly. If for example and not limitation the peripheral device takes too much time to respond to the message the VMC may time-out waiting for the peripherals response message. As a result the system 500 could fail to initialize and operate correctly.

USA-010

- 17 -

Item #38

Replace the paragraph on page 76 lines 9-14 with the following paragraph:

Q38 In decision block 1214 the transceiver system 700 makes a determination as to whether the data received from the system 500 is data intended for system 700 configurations. System 700 can be referred to as the base unit or base. If the resultant is in the affirmative that is the data is configuration data for the base unit processing moves to block 1218. If the resultant is in the negative that is the data is not configuration data for the base unit then processing moves to block 1216.

Item #39

Replace the paragraph on page 78 lines 8-9 with the following paragraph:

Q39 In block 1232 the transceiver system 700 sends the ACK message to the system 500 originating the data command. Processing then moves to block 1238.

Item #40

Replace the paragraph on page 78 lines 15-16 with the following paragraph:

Q40 In block 1240 the transceiver system 700 sends the ACK message to the system 500 originating the data command. Processing then move back to block 1208.

Item #41

Q41 Replace the paragraph starting on page 78 line 22 through page 79 line 3 with the following paragraph:

Referring to Figure 13 there is shown a local transaction authorization routine 1300. A conventional card authorization through a remote processing bureau utilizing

USA-010

- 18 -

Q41
dial-up landline access to the remote processing bureau can take ten or more seconds to complete. In certain vending venues and or while vending certain type of products a ten or more second delay may be unacceptable. In these instances authorization routine 1300 can be implemented to reduce or eliminate the authorization delay while maintaining a high confidence that the card is valid. A card can be any form of ID including a credit card, private label card, smart card, hotel room card, RFID, biometric, and or other similar or suitable form of ID. Processing begins in decision block 1302.

Item #42

Replace the paragraph on page 79 lines 5-10 with the following paragraph:

Q42
In decision block 1302 a determination is made as to whether the LOCAL AUTHORIZATION flag is set for this pass. In an exemplary embodiment system 500 can be programmed to locally authorize a card based in part on an iterative process, which allows for the local authorization routine to be invoked, at a minimum, on the first pass and subsequently at any successive pass, up to the last pass. The last pass is predetermined and is referred to as the MAXIMUM AUTHORIZATION ATTEMPTS.

Item #43

Replace the paragraph on page 83 lines 5-11 with the following paragraph:

Q43
In block 1410 a batch of locally authorized transactions is data communicated to a remote location (the remote location being another country) by way of a network connection. In this regard locally authorized transactions can be moved from the country in which the vending sale occurred to the country where the transactions will be processed with a processing center. Processing then moves to block 1412. The transfer of locally authorized transactions can occur at a predetermined time including hourly, daily, weekly, monthly, or other desirable time interval.

USA-010

- 19 -

Item #44

Replace the paragraph on page 85 lines 4-8 with the following paragraph:

944
In block 1504 the system 500 terminal configuration data is exchanged between the system 500 and the host network servers. This terminal configuration data effectuates the ability to remotely manage the terminal operational parameters including the terminals firmware version from a remote host network center 808. Processing then moves to block 1506.

Item #45

Replace the paragraph on page 87 lines 22-26 with the following paragraph:

945
In decision block 1624 a determination is made as to whether the user has pressed the end transaction button. If the resultant is in the affirmative that is the user has pressed the end transaction button then processing moves to block 1626. If the resultant is in the negative that is the user has not pressed the end transaction button then processing moves to decision block 1628.

Item #46

Replace the paragraph on page 88 lines 7-9 with the following paragraph:

946
In block 1630 the VEND REQUEST command is processed and a VEND APPROVED or VEND DENIED response message is data communicated from the system 500 to the requesting VMC. Processing then moves to decision block 1632.

Item #47

Replace the paragraph on page 89 lines 1-2 with the following paragraph:

USA-010

- 20 -

Q47
In block 1636 the RE-VEND TIMER is reset to zero. Processing then moves to block 1640.

Item #48

Replace the paragraph on page 89 lines 9-14 with the following paragraph:

Q48
In decision block 1642 a determination is made as to whether the RE-VEND TIMER has reached the RE-VEND TIMER LIMIT. If the resultant is in the affirmative that is the RE-VEND TIMER has reached the RE-VEND TIMER LIMIT then processing moves back to block 1626. If the resultant is in the negative that is the RE-VEND TIMER has been reached the RE-VEND TIMER LIMIT then processing moves to decision block 1646.

Item #49

Replace the paragraph on page 89 lines 16-20 with the following paragraph:

Q49
In decision block 1646 a determination is made as to whether the user has pressed the end transaction button. If the resultant is in the affirmative that is the user has pressed the end transaction button then processing moves back to block 1626. If the resultant is in the negative that is the user has not pressed the end transaction button then processing moves to block 1644.

Item #50

Replace the paragraph on page 89 lines 22-26 with the following paragraph:

Q50
In decision block 1644 a determination is made as to whether a VEND REQUEST MDB command has been received from the vending equipment's VMC. If

USA-010

- 21 -

Q50
the resultant is in the affirmative that is the VEND REQUEST has been received then processing moves to block 1648. If the resultant is in the negative that is the VEND REQUEST command was not received then processing moves back to decision block 1642.

Item #51

Replace the paragraph on page 90 lines 1-3 with the following paragraph:

Q51
In block 1648 the VEND REQUEST command is processed and a VEND APPROVED or VEND DENIED response message is data communicated from the system 500 to the requesting VMC. Processing then moves to back to decision block 1632.

Item #52

Replace the paragraph on page 90 lines 5-11 with the following paragraph:

Q52
Referring to Figure 17 there is shown a data communication sweeping, processing, and data forwarding routine 1700. In an exemplary embodiment the host network center 808 accumulates a plurality of different kinds of parsed data transactions in a temporary data structure. Such a parsing and temporary data structure can be implemented as disclosed in routine 1500. To move the data transactions from the temporary data structure a more permanent data structure and or host network sever routine 1700 can be implemented. Processing begins in block 1702.

Item #53

Replace the paragraph on page 90 lines 13-16 with the following paragraph:

USA-010

- 22 -

Q53
In block 1702 the transactions stored in the temporary data structure are swept into an operational database. Such an operational database can be implemented as a SQL database, ORACLE database, flat file database, DB2 database, and or a combination of different kinds and types of databases. Processing then moves to block 1704.

Item #54

Replace the paragraph on page 90 lines 23-27 with the following paragraph:

Q54
In block 1706 any transactions includeing the previously posted authorized transactions are settled with the processing bureau 804. The process of settlement effectuates the transfer of funds from the cardholder to the merchant. Settlement after the vending sale has occurred can be referred to as post settlement or post settle. Processing then moves to block 1708.

Item #55

Replace the paragraph on page 91 lines 1-7 with the following paragraph:

Q55
In block 1708 any refund transactions generated by the host network center customer service are processed. Refund transactions can occur when a previously settled transaction requires some portion of the sale amount be refunded to the cardholder. Customer service can generate a refund transaction by querying from an operation database the original transaction and then initiate a refund transaction based in part on the queried customer's original transaction. Processing then moves to block 1710.

Item #56

Replace the paragraph on page 91 lines 15-22 with the following paragraph:

USA-010

- 23 -

Q56
In addition to the convert and forward functionality the data handled can be measured and counted as desired for the purpose of billing for the service of gathering data from a remote system 500 and delivering the data to a customer's desired location. Measurement and counting can include for example and not limitation measuring file and or data size, measuring the frequency the data is gathered, counting the number of times data is gathered and or forwarded, measuring access to the host network center 808, or by other suitable measurement and counting method and or criteria. Processing moves to block 1712.

Item #57

Replace the paragraph starting on page 91 line 24 through page 92 line 2 with the following paragraph:

Q57
In block 1712 the funds collected from the processing of transactions can be remitted to the customer as required by EFT or other desirable method. The funds remitted can have service fees deducted from them such that their EFT amount is less than the total processed transaction amount. In this regard customer will not have to be billed for services. The deducting of service fees from the flow of funds can eliminate the need to invoice a customer for service. The routine is then exited.

Item #58

Replace the paragraph on page 92 lines 14-17 with the following paragraph:

Q58
In block 1802 the VMC and system 500 exchange MDB message commands by way of the VMC MDB interface 902 and the system 500's MDB interface 518. The system 500 can be referred to as terminal 500 or as the terminal. Processing moves to block 1804.

USA-010

- 24 -

Item #59

Replace the paragraph on page 93 lines 6-11 with the following paragraph:

959
In block 1810 the system 500 by way of the mimic MDB interface 516 receives any response MDB message from the coin mechanism. As required the system 500 decodes and determines if the response message from the coin mechanism requires encoding and forwarding or passing of the message to the VMC. As determined by the system 500 the message is selectively forwarded to the VMC upon processing returning to block 1802.

Item #60

Replace the paragraph on page 93 lines 13-18 with the following paragraph:

960
In decision block 1812 a determination is made as to whether the MDB command message is a bill acceptor command message. If the resultant is in the affirmative that is the MDB command message is a bill acceptor MDB command message then processing moves to block 1814. If the resultant is in the negative that is the MDB command message is not a bill acceptor MDB command message then processing moves to decision block 1818.

Item #61

Replace the paragraph on page 93 lines 20-22 with the following paragraph:

961
In block 1814 the MDB command message is encoded and forwarded or passed by way of the mimic MDB interface 516 to the bill acceptor. Processing then moves to block 1816.

USA-010

- 25 -

Item #62

Replace the paragraph starting on page 93 line 24 through page 94 line 2 with the following paragraph:

Q62
In block 1816 the system 500 by way of the mimic MDB interface 516 receives any response MDB message from the bill acceptor. As required the system 500 decodes and determines if the response message from the bill acceptor requires encoding and forwarding or passing of the message to the VMC. As determined by the system 500 the message is selectively forwarded to the VMC upon processing returning to block 1802.

Item #63

Replace the paragraph on page 94 lines 4-9 with the following paragraph:

Q63
In decision block 1818 a determination is made as to whether the MDB command message is a card reader or online module (OLM) command message. If the resultant is in the affirmative that is the MDB command message is a card reader or OLM MDB command message then processing moves to block 1820. If the resultant is in the negative that is the MDB command message is not a card reader or OLM MDB command message then processing moves to block 1822.

Item #64

Replace the paragraph on page 95 lines 6-7 with the following paragraph:

Q64
In block 1826 the terminal system 500 can manage the data received from the peripheral device as required. Processing moves back to block 1802.

126

a